according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Frostox® SF-D12++öko

Product code : 10189

Unique Formula Identifier : \$140-Y088-6006-W8HT

(UFI)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Radiator anti-freeze

stance/Mixture

Recommended restrictions

on use

: Not applicable

1.3 Details of the supplier of the safety data sheet

Company : HAERTOL Chemie GmbH

Havelstr. 21

39126 Magdeburg

Telephone : +49 391 2800 231

Telefax : +49 391 2800 280

E-mail address of person

responsible for the SDS

: info@haertol.de

1.4 Emergency telephone number

+49 6132 / 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Reproductive toxicity, Category 1B H360D: May damage the unborn child.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H360D May damage the unborn child.

H373 May cause damage to organs through prolonged or

repeated exposure.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON

CENTER/ doctor if you feel unwell. Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

Ethylene glycol

2-Ethylhexanoic acid

Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Ethylene glycol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 70 - < 90
	01 2113430010 20	Acute toxicity esti- mate	
		Acute oral toxicity: 1.330 mg/kg	
2-Ethylhexanoic acid	149-57-5 205-743-6 607-230-00-6	Repr. 1B; H360D	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox®SF-D12++öko

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 2.0 05.05.2023 4226710-00010 Date of first issue: 26.04.2019

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks Harmful if swallowed.

May damage the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- : Carbon oxides

ucts

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapours.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national

regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

Storage class (TRGS 510) : 6.1C

Storage period : 60 Months

Recommended storage tem-

perature

> -25 °C

Dampness : Keep in a dry place.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Commonanta	CACNE	Malua tura /Farra	Control managed and	Dania
Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Ethylene glycol	107-21-1	TWA	20 ppm	2000/39/EC
			52 mg/m3	
	Further inform	Further information: Identifies the possibility of significant uptake through the		
	skin, Indicative	skin, Indicative		
		STEL	40 ppm	2000/39/EC
			104 mg/m3	
	Further inform	Further information: Identifies the possibility of significant uptake through the		
	skin, Indicative	skin, Indicative		
		AGW (Vapour	10 ppm	DE TRGS
		and aerosols)	26 mg/m3	900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL			
	and biological tolerance values, there is no risk of harming the unborn child			
Glycerine	56-81-5	AGW (Inhalable	200 mg/m3	DE TRGS

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

I	fraction)		900
	Peak-limit: excursion factor (category): 2;(l)		
l	Further information: When there is compliance with the OEL and biological		d biological
	tolerance values, there is no risk of harming the unborn child		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethylene glycol	Workers	Inhalation	Long-term local effects	35 mg/m3
	Workers	Skin contact	Long-term systemic effects	106 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	53 mg/kg bw/day
2-Ethylhexanoic acid	Workers	Inhalation	Long-term systemic effects	14 mg/m3
	Workers	Skin contact	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1 mg/kg bw/day
Glycerine	Workers	Inhalation	Long-term local effects	56 mg/m3
	Consumers	Ingestion	Long-term systemic effects	229 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	33 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Ethylene glycol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	37 mg/kg
	Marine sediment	3,7 mg/kg
	Soil	1,53 mg/kg
2-Ethylhexanoic acid	Fresh water	0,36 mg/l
	Marine water	0,036 mg/l
	Intermittent use/release	0,493 mg/l
	Sewage treatment plant	71,7 mg/l
	Fresh water sediment	6,37 mg/kg
	Marine sediment	0,637 mg/kg
	Soil	1,06 mg/kg
Glycerine	Fresh water	0,885 mg/l
	Marine water	0,0885 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

II	Intermittent use/release	8,85 mg/l
	Sewage treatment plant	1000 mg/l
	Fresh water sediment	3,3 mg/kg dry weight (d.w.)
	Marine sediment	0,33 mg/kg dry weight (d.w.)
	Soil	0,141 mg/kg dry weight (d.w.)
Sebacic acid	Fresh water	0,018 mg/l
	Marine water	0,0018 mg/l
	Intermittent use/release	0,18 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,547 mg/kg
	Marine sediment	0,0547 mg/kg
	Soil	0,0986 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety glasses

Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : > 30 min
Glove thickness : 0,7 mm

Directive : Equipment should conform to DIN EN 374

Protective index : Class 2

Material : Nitrile rubber
Break through time : > 30 min
Glove thickness : 0,4 mm

Directive : Equipment should conform to DIN EN 374

Protective index : Class 2

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Organic vapour type (A)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : violet

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

> 170 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : > 110 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 8,4

Concentration: 100 %

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : in all proportions

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

Partition coefficient: n-

octanol/water

: Not applicable

Vapour pressure : No data available

Density : 1,138 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Substances and mixtures, which in contact with water, emit flammable gases

: The substance or mixture does not emit flammable gases in

contact with water.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation exposure Skin contact

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

Ingestion Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1.822 mg/kg

Method: Calculation method

Components:

Ethylene glycol:

Acute oral toxicity : Acute toxicity estimate: 1.330 mg/kg

Method: Expert judgement

Acute inhalation toxicity : LC50 (Rat): > 2,5 mg/l

Exposure time: 6 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Mouse): > 3.500 mg/kg

2-Ethylhexanoic acid:

Acute oral toxicity : LD50 (Rat): 2.043 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethylene glycol:

Species : Rabbit

Result : No skin irritation

2-Ethylhexanoic acid:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Ethylene glycol:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

Species : Rabbit

Result : No eye irritation

2-Ethylhexanoic acid:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Ethylene glycol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

2-Ethylhexanoic acid:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

2-Ethylhexanoic acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

Germ cell mutagenicity- As-

sessment Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Ethylene glycol:

Species: MouseApplication Route: IngestionExposure time: 2 YearsResult: negative

Reproductive toxicity

May damage the unborn child.

Components:

2-Ethylhexanoic acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: positive

Reproductive toxicity - As-

sessment

: Clear evidence of adverse effects on development, based on

animal experiments.

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

Ethylene glycol:

Exposure routes : Ingestion
Target Organs : Kidney

Assessment : Shown to produce significant health effects in animals at con-

centrations of >10 to 100 mg/kg bw.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox®SF-D12++öko

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 2.0 05.05.2023 4226710-00010 Date of first issue: 26.04.2019

Repeated dose toxicity

Components:

Ethylene glycol:

Species Rat NOAEL 150 mg/kg Application Route Ingestion Exposure time 2 yr

Species Dog

NOAEL 2.200 - 4.400 mg/kg

Skin contact Application Route Exposure time : 4 Weeks

OECD Test Guideline 410 Method

2-Ethylhexanoic acid:

Species Rat NOAEL 300 mg/kg Application Route Ingestion Exposure time 91 - 93 Days

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethylene glycol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 72.860 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 6.500 -

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox®SF-D12++öko

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 2.0 05.05.2023 4226710-00010 Date of first issue: 26.04.2019

plants 13.000 mg/l

Exposure time: 96 h

Toxicity to fish (Chronic tox-

icity)

NOEC: 15.380 mg/l Exposure time: 7 d

Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 8.590 mg/l Exposure time: 7 d

Species: Ceriodaphnia dubia (water flea)

2-Ethylhexanoic acid:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 106 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): 49,3 mg/l

Exposure time: 72 h

Toxicity to microorganisms EC50 (Pseudomonas putida): 112,1 mg/l

Exposure time: 17 h

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 25 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

Ethylene glycol:

Biodegradability Result: Readily biodegradable. Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301A

2-Ethylhexanoic acid:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 99 % Exposure time: 28 d

Method: OECD Test Guideline 301E

12.3 Bioaccumulative potential

Components:

Ethylene glycol:

Bioaccumulation Species: Leuciscus idus (Golden orfe)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

Bioconcentration factor (BCF): 10

Partition coefficient: n-

octanol/water

: log Pow: -1,93

2-Ethylhexanoic acid:

Partition coefficient: n-

octanol/water

log Pow: 2,7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox®SF-D12++öko

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 2.0 05.05.2023 4226710-00010 Date of first issue: 26.04.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 75, 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. mixtures and articles (Annex XVII)

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

: WGK 1 slightly hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H302 : Harmful if swallowed.

H360D : May damage the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Repr. : Reproductive toxicity

STOT RE : Specific target organ toxicity - repeated exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency: EC-Number - European Community number: ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Frostox® SF-D12++öko

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 2.0
 05.05.2023
 4226710-00010
 Date of first issue: 26.04.2019

Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Acute Tox. 4 H302 Calculation method
Repr. 1B H360D Calculation method
STOT RE 2 H373 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN