



DESCRIPTION

FROSTOX® S is an acidic cooling system cleaner for use in internal combustion engines. It easily removes deposits from the cooling system. **FROSTOX® S** is based on monoethylene glycol, contains organic acid corrosion inhibitors, is silicate free, and provides mild and gentle cleansing of cooling systems. **FROSTOX® S** is suitable for use with cast iron and all-aluminium engines.

OEM APPROVALS

FROSTOX® S is approved by the following manufacturers:

Audi: VW G1100001

Skoda: VW G1100001

Seat: VW G1100001

Volkswagen: VW G1100001

PHYSICAL AND CHEMICAL PROPERTIES





	Value	Method
Density at 20°C [g/cm ³]	1.080–1.110	DIN 51757
pH value (33% aqueous solution)	4.8–5.2	ASTM D1287

PERFORMANCE CHARACTERISTICS

The mixture ratio should be 1 part cleaner to 3–4 parts water. The cooling system of the vehicle is cleaned for approximately 15 minutes with the engine running after the thermostat has opened. Drain the cleaning fluid and repeat as necessary. Then rinse the cooling system twice with the thermostat open. Re-fill with coolant in accordance with manufacturer guidelines.

CONTAINER AND DELIVERY SPECIFICATIONS

FROSTOX® S is dyed yellow. The following container sizes are available:

	1	1.5 litre		3	5	10	20	30 litre
	60	200 litre		20 to 24 tons				

Please inquire for additional container sizes if required.