

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ OEM Advanced 48

Unique Formula Identifier (UFI) : 3RA0-F037-200S-HVYU

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Anti-freezing agents

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : HAERTOL Chemie GmbH
Havelstr. 21
39126 Magdeburg

Telephone : +49 391 2800 231

Telefax : +49 391 2800 280

E-mail address of person responsible for the SDS : info@haertol.de

1.4 Emergency telephone number

+49 6132 / 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Reproductive toxicity, Category 1B	H360FD: May damage fertility. May damage the unborn child.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H360FD May damage fertility. May damage the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
Storage:
P405 Store locked up.

Hazardous components which must be listed on the label:

Ethylene glycol
Sodium 2-ethylhexanoate
Disodium tetraborate, anhydrous

Additional Labelling

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version 1.1 Revision Date: 09.10.2025 SDS Number: 11535212-00002 Date of last issue: 13.05.2025
Date of first issue: 13.05.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Ethylene glycol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney) Acute toxicity estimate Acute oral toxicity: 500 mg/kg	>= 90 - <= 100
Sodium 2-ethylhexanoate	19766-89-3 243-283-8 607-230-00-6	Repr. 1B; H360D	>= 1 - < 10
Disodium sebacate	17265-14-4 241-300-3 01-2120762063-61	Eye Irrit. 2; H319	>= 1 - < 10
Disodium tetraborate, anhydrous	1330-43-4 215-540-4 005-011-00-4 01-2119490790-32	Eye Irrit. 2; H319 Repr. 1B; H360FD	>= 0,3 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful if swallowed.
May damage fertility. May damage the unborn child.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe the mist or vapours.
Do not swallow.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version 1.1 Revision Date: 09.10.2025 SDS Number: 11535212-00002 Date of last issue: 13.05.2025
Date of first issue: 13.05.2025

Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

Storage class (TRGS 510) : 6.1C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethylene glycol	107-21-1	TWA	20 ppm 52 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	40 ppm 104 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour and aerosols)	10 ppm 26 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version 1.1 Revision Date: 09.10.2025 SDS Number: 11535212-00002 Date of last issue: 13.05.2025
Date of first issue: 13.05.2025

	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	10 ppm 26 mg/m ³	DE DFG MAK
	Peak-limit: excursion factor (category): 2; I			
	Further information: Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
Disodium tetra-borate, anhydrous	1330-43-4	AGW (Inhalable fraction)	0,5 mg/m ³ (Borate)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK (inhalable fraction)	0,75 mg/m ³ (Boron)	DE DFG MAK
	Peak-limit: excursion factor (category): 1; I			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethylene glycol	Workers	Inhalation	Long-term local effects	35 mg/m ³
	Workers	Skin contact	Long-term systemic effects	106 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	7 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	53 mg/kg bw/day
Disodium sebacate	Workers	Inhalation	Long-term systemic effects	35,26 mg/m ³
	Workers	Dermal	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m ³
	Consumers	Dermal	Long-term systemic effects	5 mg/kg bw/day
Sodium 2-ethylhexanoate	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	14 mg/m ³
	Workers	Skin contact	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,5 mg/m ³
Disodium tetraborate,	Consumers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	6,7 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version 1.1 Revision Date: 09.10.2025 SDS Number: 11535212-00002 Date of last issue: 13.05.2025
Date of first issue: 13.05.2025

anhydrous			effects	
	Workers	Inhalation	Long-term local effects	11,7 mg/m3
	Workers	Inhalation	Acute local effects	17,7 mg/m3
	Workers	Skin contact	Long-term systemic effects	316,4 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,4 mg/m3
	Consumers	Inhalation	Long-term local effects	11,7 mg/m3
	Consumers	Inhalation	Acute local effects	11,7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	159,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,79 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,79 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Ethylene glycol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	37 mg/kg
Disodium sebacate	Marine sediment	3,7 mg/kg
	Soil	1,53 mg/kg
	Fresh water	0,018 mg/l
	Intermittent use/release	0,18 mg/l
	Marine water	0,002 mg/l
Sodium 2-ethylhexanoate	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,548 mg/kg dry weight (d.w.)
	Marine sediment	0,055 mg/kg dry weight (d.w.)
	Soil	0,099 mg/kg dry weight (d.w.)
	Fresh water	0,36 mg/l
Disodium tetraborate, anhydrous	Freshwater - intermittent	0,493 mg/l
	Marine water	0,036 mg/l
	Sewage treatment plant	71,7 mg/l
	Fresh water sediment	0,301 mg/kg dry weight (d.w.)
	Marine sediment	0,03 mg/kg dry weight (d.w.)
Disodium tetraborate, anhydrous	Soil	0,058 mg/kg dry weight (d.w.)
	Fresh water	2,9 mg/l
	Marine water	2,9 mg/l
	Intermittent use/release	13,7 mg/l
	Sewage treatment plant	10 mg/l
	Soil	5,7 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : > 30 min
Glove thickness : 0,7 mm
Guideline : Equipment should conform to DIN EN 374
Protective index : Class 2

Material : Nitrile rubber
Break through time : > 30 min
Glove thickness : 0,4 mm
Guideline : Equipment should conform to DIN EN 374
Protective index : Class 2

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Filter should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Form : liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Colour	:	blue green
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	> 165 °C
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	100 - < 200 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	7,1 - 7,3 Concentration: 100 %
Viscosity Viscosity, kinematic	:	20 - 30 mm ² /s
Solubility(ies) Water solubility	:	in all proportions
Partition coefficient: n-octanol/water	:	Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Vapour pressure : 0,2 hPa

Relative density : No data available

Density : 1,122 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 525,7 mg/kg
Method: Calculation method

Components:

Ethylene glycol:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Expert judgement

Acute inhalation toxicity : LC50 (Rat): > 2,5 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Mouse): > 3.500 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Sodium 2-ethylhexanoate:

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Disodium sebacate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Disodium tetraborate, anhydrous:

Acute oral toxicity : LD50 (Rat): > 2.500 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version 1.1 Revision Date: 09.10.2025 SDS Number: 11535212-00002 Date of last issue: 13.05.2025
Date of first issue: 13.05.2025

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2,03 mg/l
Exposure time: 5 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethylene glycol:

Species : Rabbit
Result : No skin irritation

Disodium sebacate:

Species : Rabbit
Result : No skin irritation

Disodium tetraborate, anhydrous:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Ethylene glycol:

Species : Rabbit
Result : No eye irritation

Disodium sebacate:

Species : Bovine cornea
Method : OECD Test Guideline 437

Species : Tissue Culture
Method : EpiOcular

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Result : Irritation to eyes, reversing within 21 days

Disodium tetraborate, anhydrous:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 7 days
Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Ethylene glycol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Sodium 2-ethylhexanoate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Disodium sebacate:

Test Type : Intracutaneous test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Disodium tetraborate, anhydrous:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Components:

Ethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Sodium 2-ethylhexanoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Remarks: Based on data from similar materials

Disodium sebacate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Disodium tetraborate, anhydrous:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Ethylene glycol:

Species : Mouse
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Disodium tetraborate, anhydrous:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

May damage fertility. May damage the unborn child.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Components:

Sodium 2-ethylhexanoate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.
Remarks: Based on data from similar materials

Disodium sebacate:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Disodium tetraborate, anhydrous:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Components:

Ethylene glycol:

Exposure routes : Ingestion
Target Organs : Kidney
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

Ethylene glycol:

Species : Rat
NOAEL : 200 mg/kg
Application Route : Ingestion
Exposure time : 33 Days

Species : Dog
NOAEL : 2.200 - 4.400 mg/kg
Application Route : Skin contact
Exposure time : 4 Weeks
Method : OECD Test Guideline 410

Sodium 2-ethylhexanoate:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

Disodium sebacate:

Species : Rat
NOAEL : >= 1.000 mg/kg
Application Route : Ingestion
Exposure time : 6 Months

Disodium tetraborate, anhydrous:

Species : Rat
NOAEL : 149 mg/kg
LOAEL : 217 mg/kg
Application Route : Ingestion
Exposure time : 9 Weeks
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

11.2 Information on other hazards

Endocrine disrupting properties

Not classified based on available information.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethylene glycol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 72.860 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Raphidocelis subcapitata (freshwater green alga)):
plants : 6.500 - 13.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : NOEC: 8.590 mg/l
aquatic invertebrates (Chronic : Exposure time: 7 d
toxicity) : Species: Ceriodaphnia dubia (water flea)

Sodium 2-ethylhexanoate:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 910 mg/l
aquatic invertebrates : Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 500
plants : mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 130
mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (*Pseudomonas putida*): > 1 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 18 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

Disodium sebacate:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Acartia tonsa* (Calanoid copepod)): > 10 - 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: ISO 14669 and PARCOM method
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOELR (*Skeletonema costatum* (marine diatom)): > 1 - 10 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: ISO 10253
Remarks: Based on data from similar materials

EL50 (*Skeletonema costatum* (marine diatom)): > 10 - 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: ISO 10253
Remarks: Based on data from similar materials

Disodium tetraborate, anhydrous:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 79,7 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Ceriodaphnia dubia* (water flea)): 91 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 52,4 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): 35 mg/l
Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 10.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: 6,4 mg/l
Exposure time: 34 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 6,4 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Ethylene glycol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301A

Sodium 2-ethylhexanoate:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301E
Remarks: Based on data from similar materials

Disodium sebacate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 89 %
Exposure time: 28 d
Method: OECD Test Guideline 306

12.3 Bioaccumulative potential

Components:

Ethylene glycol:

Partition coefficient: n-octanol/water : log Pow: -1,36
Remarks: Calculation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

Sodium 2-ethylhexanoate:

Partition coefficient: n-octanol/water : log Pow: 1,3
Method: OECD Test Guideline 117

Disodium sebacate:

Partition coefficient: n-octanol/water : log Pow: -4,9

Disodium tetraborate, anhydrous:

Partition coefficient: n-octanol/water : log Pow: -1,53

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

ding site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 3 Number on list 30: Sodium 2-ethylhexanoate, Disodium tetraborate, anhydrous Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor. Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Disodium tetraborate, anhydrous
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.		Not applicable
Water hazard class (Germany)	:	WGK 1 slightly hazardous to water Classification according to AwSV, Annex 1 (5.2)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

TA Luft List (Germany) : 5.2.7.1.3: Substances toxic to reproduction:
Sodium 2-ethylhexanoate, Disodium tetraborate, anhydrous

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H302 : Harmful if swallowed.
H319 : Causes serious eye irritation.
H360D : May damage the unborn child.
H360FD : May damage fertility. May damage the unborn child.
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity
STOT RE : Specific target organ toxicity - repeated exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE DFG MAK : Germany. MAK BAT Annex IIa
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
DE DFG MAK / MAK : MAK value
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regula-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Valvoline™ OEM Advanced 48

Version	Revision Date:	SDS Number:	Date of last issue: 13.05.2025
1.1	09.10.2025	11535212-00002	Date of first issue: 13.05.2025

tion (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Acute Tox. 4

H302

Repr. 1B

H360FD

STOT RE 2

H373

Classification procedure:

Calculation method

Calculation method

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN